

# LANDING OBLIQUE VALVE



## SPECIFICATIONS

Type	Screw Type (Thread)
Size	Diameter - 65 mm (2 1/2")
Working Pressure	16 Bar
Test Pressure	30 Bar
Flow Rate	4.5 Bar/Litre
Inlet Size	65 mm BSP Thread
Outlet Size	BS336 Female Instantaneous
Material	Copper Alloy (Body) ; Cast Iron (Wheel)
Finishing	Red

Specifications are subject to change without prior notice.

## DEMCO ADVANTAGES

- Suitable to Install in Wet Riser
- Robust Design and Long Lasting
- Copper Alloy to BS 1982
- Grey Cast Iron to BS EN 1561
- Pressure Test - 7 Bar
- Manufacture and certified to BS 5041 Part 1\*

 **DEMCO**  
INDUSTRIES SDN BHD  
[www.demcoalarm.com](http://www.demcoalarm.com)

Lot 3928, Jalan Keretapi Lama  
Off Jalan Kapar 5 1/2 Miles  
42100 Klang  
Selangor Darul Ehsan  
West Malaysia  
Tel: 603-3290 3333  
Fax: 603-3290 2288  
E-mail: [sales@demcoalarm.com](mailto:sales@demcoalarm.com)



CERTIFIED TO BS 5541 PART 1  
LICENCE NO. KM85754

SIRIM  
CERTIFIED TO BS 5541 PT-1:1987  
Certification No: PS005706

Quality without Compromise